

Safety Data Sheet

Conforms to Regulation (EC) No. 1907/2006 (REACH), Article 31, Annex II, as amended by Commission Regulation (EU) 2020/878

KERABUILD EPOFILL (A)

Date of first edition: 10/8/2021

Safety Data Sheet dated 10/3/2022

version 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: KERABUILD EPOFILL (A)

Trade code: B0020 .030

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Epoxy coating

Uses advised against: Not available

1.3. Details of the supplier of the safety data sheet

Company: KERAKOLL S.p.A.

Via dell'Artigianato, 9

41049 Sassuolo (MODENA) - ITALY

Tel.+39 0536 816511 Fax. +39 0536816581

safety@kerakoll.com

1.4. Emergency telephone number

European emergency phone number 112

Kerakoll Italy - +39-0536-816511

Ireland

Poison information centre: 01 809 2166 (Daily 8am-10pm)

In case of emergency call 999 or 112

Malta

In case of emergency call: +356 2395 2000 (24h)

SECTION 2: Hazards identification



2.1. Classification of the substance or mixture

Regulation (EC) n. 1272/2008 (CLP)

Skin Irrit. 2 Causes skin irritation.

Eye Irrit. 2 Causes serious eye irritation.

Skin Sens. 1B May cause an allergic skin reaction.

Aquatic Chronic 2 Toxic to aquatic life with long lasting effects.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Regulation (EC) No 1272/2008 (CLP):

Pictograms and Signal Words



Warning

Hazard statements

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

- P273 Avoid release to the environment.
- P302+P352 IF ON SKIN: Wash with plenty of water.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P501 Dispose of contents/container in accordance with applicable regulations.

Contains

oxirane, mono[(C12-14-alkyloxy)methyl] derivs.
bis-[4-(2,3-epoxipropoxy)phenyl]propane
Bisphenol-F-epichlorohydrin resin

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

2.3. Other hazards

No PBT, vPvB or endocrine disruptor substances present in concentration $\geq 0.1\%$.

Other Hazards: No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Mixture identification: KERABUILD EPOFILL (A)

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Numb.	Classification	Registration Number
50-75 %	bis-[4-(2,3-epoxipropoxy)phenyl]propane	CAS:1675-54-3 EC:216-823-5 Index:603-073-00-2	Eye Irrit. 2, H319 Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411, M-Chronic:1 Specific Concentration Limits: C $\geq 5\%$: Eye Irrit. 2 H319 C $\geq 5\%$: Skin Irrit. 2 H315	01-2119456619-26
20-24,9 %	oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	CAS:68609-97-2 EC:271-846-8 Index:603-103-00-4	Skin Irrit. 2, H315; Skin Sens. 1B, H317	01-2119485289-22
20-24,9 %	Bisphenol-F-epichlorohydrin resin	CAS:9003-36-5 EC:500-006-8	Skin Irrit. 2, H315; Skin Sens. 1, H317; Aquatic Chronic 2, H411, M-Chronic:1	01-2119454392-40

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

- Immediately take off all contaminated clothing.
- Remove contaminated clothing immediately and dispose off safely.
- After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

- After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.
- Protect uninjured eye.

In case of Ingestion:

- Do not induce vomiting, get medical attention showing the SDS and label hazardous.

In case of Inhalation:

- Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

Eye irritation
Eye damages
Skin Irritation
Erythema

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Water.

Carbon dioxide (CO₂).

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove persons to safety.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Wash with plenty of water.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

7.2. Conditions for safe storage, including any incompatibilities

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

7.3. Specific end use(s)

Recommendation(s)

None in particular

Industrial sector specific solutions:

None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Community Occupational Exposure Limits (OEL)

Component	OEL Type	Country	Ceiling	Long Term mg/m ³	Long Term ppm	Short Term mg/m ³	Short Term ppm	Notes
bis-[4-(2,3-epoxipropoxy)phenyl]propane	NATIONAL	NETHERLANDS		5.000				respirable fraction

Predicted No Effect Concentration (PNEC) values

Component	CAS-No.	PNEC Limit	Exposure Route	Exposure Frequency
bis-[4-(2,3-epoxipropoxy)phenyl] propane	1675-54-3	0.006 mg/l	Freshwater	
		600.000 ng/L	Marine water	
		0.996 mg/kg	Freshwater sediments	
		0.099 mg/kg	Marine water sediments	
		0.196 mg/kg	Soil	
		10.000 mg/l	Microorganisms in sewage treatments	
		0.018 mg/l	Intermittent releases (freshwater)	
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	68609-97-2	0.007 mg/l	Freshwater	
		0.072 µg/l	Marine water	
		10.000 mg/l	Microorganisms in sewage treatments	
		66.770 mg/kg	Freshwater sediments	
		6.677 mg/kg	Marine water sediments	
		80.120 mg/kg	Soil	
		0.072 mg/l	Intermittent releases (freshwater)	

Derived No Effect Level (DNEL) values

Component	CAS-No.	Worker Industry	Worker Professional	Consumer	Exposure Route	Exposure Frequency
bis-[4-(2,3-epoxipropoxy)phenyl] propane	1675-54-3		0.750 mg/kg		Human Oral	Long Term, local effects
			0.750 mg/kg		Human Oral	Long Term, systemic effects
			3.571 mg/kg		Human Dermal	Long Term, systemic effects
			3.571 mg/kg		Human Dermal	Long Term, local effects
			12.250 mg/m ³		Human Inhalation	Long Term, systemic effects
			12.250 mg/m ³		Human Inhalation	Long Term, local effects
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	68609-97-2		17.000 mg/kg	10.000 mg/kg	Human Dermal	Short Term, systemic effects
			29.000 mg/m ³	7.600 mg/m ³	Human Inhalation	Short Term, systemic effects
				1219.000 mg/kg	Human Oral	Short Term, systemic effects
			68.000 mg/kg	40.000 mg/kg	Human Dermal	Short Term, local effects
			9.800 mg/m ³	2.900 mg/m ³	Human Inhalation	Short Term, local effects
			3.900 mg/kg	2.350 mg/kg	Human Dermal	Long Term, systemic effects

13.800 mg/m ³	4.100 mg/m ³	Human Inhalation	Long Term, systemic effects
	1.000 mg/kg	Human Oral	Long Term, systemic effects
1.700 mg/kg	1.000 mg/kg	Human Dermal	Long Term, local effects
0.980 mg/kg	1.460 mg/kg	Human Inhalation	Long Term, local effects

8.2. Exposure controls

Eye protection:

Eye glasses with side protection.

Protection for skin:

Safety shoes.

Protection for hands:

Neoprene, Nitrile rubber.

Respiratory protection:

N.A.

Thermal Hazards:

N.A.

Environmental exposure controls:

N.A.

Hygienic and Technical measures

N.A.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical State Solid

Color: Yellow

Odour: Light

Odour threshold: N.A.

pH: N.A.

Kinematic viscosity: N.A.

Melting point / freezing point: N.A.

Initial boiling point and boiling range: 278 °C (532 °F)

Flash point: 141 °C (286 °F)

Upper/lower flammability or explosive limits: N.A.

Vapour density: N.A.

Vapour pressure: N.A.

Relative density: 1.11 g/cm³ (EN 1097-03)

Solubility in water: Soluble

Solubility in oil: N.A.

Partition coefficient (n-octanol/water): N.A.

Auto-ignition temperature: N.A.

Decomposition temperature: N.A.

Flammability: N.A.

Volatile Organic compounds - VOCs = 0 % ; 0 g/l

Particle characteristics:

Particle size: N.A.

9.2. Other information

Miscibility: N.A.

Conductivity: N.A.

Evaporation rate: N.A.

Viscosity: 686.00 cPo

No other relevant information

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Data not available.

10.3. Possibility of hazardous reactions

None.

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

None in particular.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological Information of the Preparation

a) acute toxicity	Not classified Based on available data, the classification criteria are not met
b) skin corrosion/irritation	The product is classified: Skin Irrit. 2(H315)
c) serious eye damage/irritation	The product is classified: Eye Irrit. 2(H319)
d) respiratory or skin sensitisation	The product is classified: Skin Sens. 1B(H317)
e) germ cell mutagenicity	Not classified Based on available data, the classification criteria are not met
f) carcinogenicity	Not classified Based on available data, the classification criteria are not met
g) reproductive toxicity	Not classified Based on available data, the classification criteria are not met
h) STOT-single exposure	Not classified Based on available data, the classification criteria are not met
i) STOT-repeated exposure	Not classified Based on available data, the classification criteria are not met
j) aspiration hazard	Not classified Based on available data, the classification criteria are not met

Toxicological information on main components of the mixture:

bis-[4-(2,3-epoxipropoxy)phenyl]propane	a) acute toxicity	LD50 Oral Rabbit = 19800.00000 mg/kg LD50 Skin Rabbit > 20.00000 mg/kg 24h	
	b) skin corrosion/irritation	Skin Irritant Rabbit Positive	epoxy resin with an average molecular mass <= 700 d irritate skin of rabbits
	c) serious eye damage/irritation	Eye Irritant Rabbit Yes	
	d) respiratory or skin sensitisation	Skin Sensitization Positive	Mouse
	f) carcinogenicity	Genotoxicity Negative Carcinogenicity Oral Rat = 15.00000 mg/kg Carcinogenicity Skin Rat = 1.00000 mg/kg	Mouse, oral NOAEL NOAEL
	g) reproductive toxicity	No Observed Effect Level Oral Rat = 750.00000 mg/kg	
	oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	a) acute toxicity	LD50 Oral Rat = 26800.00000 mg/kg LC50 Inhalation Rat > 0.20600 mg/l 4h LD50 Skin Rabbit > 4.50000 ml/Kg 24h
b) skin corrosion/irritation		Skin Irritant Rabbit Yes	
c) serious eye damage/irritation		Eye Irritant Rabbit Yes	
d) respiratory or skin sensitisation		Skin Sensitization Guinea pig Positive	

	g) reproductive toxicity	No Observed Adverse Effect Level Skin Rat = 200.00000 mg/kg
Bisphenol-F-epichlorohydrin resin	b) skin corrosion/irritation	Skin Irritant Positive
	c) serious eye damage/irritation	Eye Irritant Yes
	d) respiratory or skin sensitisation	Skin Sensitization Positive

11.2 Information on other hazards

Endocrine disrupting properties:

No endocrine disruptor substances present in concentration $\geq 0.1\%$

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

Toxic to aquatic life with long lasting effects.

List of Eco-Toxicological properties of the product

The product is classified: Aquatic Chronic 2(H411)

List of Eco-Toxicological properties of the components

Component	Ident. Numb.	Ecotox Data
bis-[4-(2,3-epoxipropoxy)phenyl]propane	CAS: 1675-54-3 - EINECS: 216-823-5 - INDEX: 603-073-00-2	a) Aquatic acute toxicity : LC50 Fish Oncorhynchus mykiss = 2.00000 mg/L 96h a) Aquatic acute toxicity : LC50 Daphnia Daphnia magna = 1.80000 mg/L 48h a) Aquatic acute toxicity : EC50 Algae Scenedesmus capricornutum = 11.00000 mg/L 72h EPA-660/3-75-009 c) Bacteria toxicity : EC50 Sludge activated sludge = 100.00000 mg/L 3h
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	CAS: 68609-97-2 - EINECS: 271-846-8 - INDEX: 603-103-00-4	a) Aquatic acute toxicity : LC50 Fish Oncorhynchus mykiss > 5000.00000 mg/L 96h a) Aquatic acute toxicity : NOEC Algae Pseudokirchneriella subcapitata = 500.00000 mg/L 72h ,,OECD Guideline 201 (Alga, Growth Inhibition Test) a) Aquatic acute toxicity : EC50 Algae Pseudokirchneriella subcapitata = 843.00000 mg/L 72h c) Bacteria toxicity : EC50 Sludge > 100.00000 mg/L

12.2. Persistence and degradability

Component	Persistence/Degradability:	Test	Value	Notes
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Non-readily biodegradable	Oxygen consumption		OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	Readily biodegradable	Oxygen consumption	87.000	%; OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)

12.3. Bioaccumulative potential

Component	Bioaccumulation	Test	Value
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Bioaccumulative	BCF - Bioconcentration factor	31.000

oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

Bioaccumulative

BCF - Bioconcentration factor 160.000

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

No PBT/vPvB Ingredients are present

12.6 Endocrine disrupting properties

No endocrine disruptor substances present in concentration \geq 0.1%

12.7 Other adverse effects

N.A.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover if possible. In so doing, comply with the local and national regulations currently in force.

A waste code according to European waste catalogue (EWC) cannot be specified, due to dependence on the usage. Contact an authorized waste disposal service.

Properties of waste which render it hazardous (Annex III, Directive 2008/98/EC):

HP 4: Irritant — skin irritation and eye damage; HP 13: Sensitising; HP 14: Ecotoxic

SECTION 14: Transport information

14.1. UN number or ID number

3082

14.2. UN proper shipping name

ADR-Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis-[4-(2,3-epoxipropoxy)phenyl]propane - Bisphenol-F-epichlorohydrin resin)

IATA-Technical name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis-[4-(2,3-epoxipropoxy)phenyl]propane - Bisphenol-F-epichlorohydrin resin)

IMDG-Technical name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis-[4-(2,3-epoxipropoxy)phenyl]propane - Bisphenol-F-epichlorohydrin resin)

14.3. Transport hazard class(es)

ADR-Class: 9

IATA-Class: 9

IMDG-Class: 9

14.4. Packing group

ADR-Packing Group: III

IATA-Packing group: III

IMDG-Packing group: III

14.5. Environmental hazards

Toxic Component most present: bis-[4-(2,3-epoxipropoxy)phenyl]propane

Marine pollutant: Yes

Environmental Pollutant: Yes

IMDG-EMS: F-A, S-F

14.6. Special precautions for user

Road and Rail (ADR-RID) :

ADR-Label: 9

ADR - Hazard identification number: 90

ADR-Special Provisions: 274 335 375 601

ADR-Transport category (Tunnel restriction code): 3 (-)

ADR Limited Quantities: 5 L

ADR Excepted Quantities: E1

Air (IATA) :

IATA-Passenger Aircraft: 964

IATA-Cargo Aircraft: 964

IATA-Label: 9

IATA-Subsidiary hazards: -

IATA-Erg: 9L

IATA-Special Provisioning: A97 A158 A197 A215

Sea (IMDG) :

IMDG-Stowage Code: Category A

IMDG-Stowage Note: -

IMDG-Subsidiary hazards: -

IMDG-Special Provisioning: 274 335 969

14.7. Maritime transport in bulk according to IMO instruments

N.A.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 605/2014 (ATP 6 CLP)

Regulation (EU) n. 2015/1221 (ATP 7 CLP)

Regulation (EU) n. 2016/918 (ATP 8 CLP)

Regulation (EU) n. 2016/1179 (ATP 9 CLP)

Regulation (EU) n. 2017/776 (ATP 10 CLP)

Regulation (EU) n. 2018/669 (ATP 11 CLP)

Regulation (EU) n. 2018/1480 (ATP 13 CLP)

Regulation (EU) n. 2019/521 (ATP 12 CLP)

Regulation (EU) n. 2020/217 (ATP 14 CLP)

Regulation (EU) n. 2020/1182 (ATP 15 CLP)

Regulation (EU) n. 2021/643 (ATP 16 CLP)

Regulation (EU) n. 2020/878

Regulation (EC) nr 648/2004 (Detergents).

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product: None

Restrictions related to the substances contained: 75

Provisions related to directive EU 2012/18 (Seveso III):

Seveso III category according to Annex 1, part 1

Lower-tier threshold (tonnes)	Upper-tier threshold (tonnes)
200	500

Product belongs to category: E2

Regulation (EU) 649/2012 (PIC regulation):

No Substance Listed

German Water Hazard Class.

Class 2: hazardous for water.

SVHC Substances:

No data available

15.2. Chemical safety assessment

A Chemical Safety Assessment has been carried out for the mixture.

SECTION 16: Other information

Code	Description
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.

Code	Hazard class and hazard category	Description
3.2/2	Skin Irrit. 2	Skin irritation, Category 2
3.3/2	Eye Irrit. 2	Eye irritation, Category 2

3.4.2/1	Skin Sens. 1	Skin Sensitisation, Category 1
3.4.2/1B	Skin Sens. 1B	Skin Sensitisation, Category 1B
4.1/C2	Aquatic Chronic 2	Chronic (long term) aquatic hazard, category 2

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008

[CLP]:

Classification according to Regulation (EC) Nr. 1272/2008 Classification procedure

3.2/2	Calculation method
3.3/2	Calculation method
3.4.2/1B	Calculation method
4.1/C2	Calculation method

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ACGIH: American Conference of Governmental Industrial Hygienists

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

AND: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

BCF: Biological Concentration Factor

BEI: Biological Exposure Index

BOD: Biochemical Oxygen Demand

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CAV: Poison Center

CE: European Community

CLP: Classification, Labeling, Packaging.

CMR: Carcinogenic, Mutagenic and Reprotoxic

COD: Chemical Oxygen Demand

COV: Volatile Organic Compound

CSA: Chemical Safety Assessment

CSR: Chemical Safety Report

DMEL: Derived Minimal Effect Level

DNEL: Derived No Effect Level.

DPD: Dangerous Preparations Directive

DSD: Dangerous Substances Directive

EC50: Half Maximal Effective Concentration

ECHA: European Chemicals Agency

EINECS: European Inventory of Existing Commercial Chemical Substances.

ES: Exposure Scenario

GefStoffVO: Ordinance on Hazardous Substances, Germany.

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

IARC: International Agency for Research on Cancer

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

IC50: half maximal inhibitory concentration

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

IMDG: International Maritime Code for Dangerous Goods.

INCI: International Nomenclature of Cosmetic Ingredients.

IRCCS: Scientific Institute for Research, Hospitalization and Health Care

KAFH: Keep Away From Heat

KSt: Explosion coefficient.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

LDLo: Leathal Dose Low

N.A.: Not Applicable
N/A: Not Applicable
N/D: Not defined/ Not available
NA: Not available
NIOSH: National Institute for Occupational Safety and Health
NOAEL: No Observed Adverse Effect Level
OSHA: Occupational Safety and Health Administration.
PBT: Persistent, Bioaccumulative and Toxic
PGK: Packaging Instruction
PNEC: Predicted No Effect Concentration.
PSG: Passengers
RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL: Short Term Exposure limit.
STOT: Specific Target Organ Toxicity.
TLV: Threshold Limiting Value.
TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
vPvB: Very Persistent, Very Bioaccumulative.
WGK: German Water Hazard Class.

Paragraphs modified from the previous revision:

- 2. HAZARDS IDENTIFICATION
- 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
- 9. PHYSICAL AND CHEMICAL PROPERTIES

Exposure Scenario

bis-[4-(2,3-epoxipropoxy)phenyl]propane

Exposure Scenario, 07/06/2021

Substance identity	
	bis-[4-(2,3-epoxipropoxy)phenyl]propane
CAS No.	1675-54-3
INDEX No.	603-073-00-2
EINECS No.	216-823-5
Registration number	01-2119456619-26

Table of contents

1. **ES 1** Widespread use by professional workers; ESC2_0000001

1. ES 1 Widespread use by professional workers; ESC2_0000001

1.1 TITLE SECTION

Exposure Scenario name	Professional application of coatings and inks - Etching agent - Resins (prepolymers) - Adhesion promotor
Date - Version	27/05/2021 - 1.0
Life Cycle Stage	Widespread use by professional workers
Main user group	Professional uses
Sector(s) of use	Professional uses (SU22)
Product Categories	ESC2_0000001
Article Category(ies)	Other articles made of stone, plaster, cement, glass or ceramic (AC4g)

Environment Contributing Scenario

CS1	ERC8c - ERC8f
------------	---------------

Worker Contributing Scenario

CS2 Material transfers	PROC8a
CS3 Rolling, Brushing	PROC10
CS4 Roller, spreader, flow application	PROC11
CS5 Mixing operations - Manual	PROC19

1.2 Conditions of use affecting exposure

1.2. CS1: Environment Contributing Scenario (ERC8c, ERC8f)

Environmental release categories	Widespread use leading to inclusion into/onto article (indoor) - Widespread use leading to inclusion into/onto article (outdoor) (ERC8c, ERC8f)
---	---

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure < 0,5 kPa at STP

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use (or from service life)

Amounts used:

Daily amount per site = 175 kg/day

Release type: Continuous release

Emission days: 365 days per year

Technical and organisational conditions and measures

Control measures to prevent releases

Provide onsite wastewater removal efficiency of ³ (%):

Conditions and measures related to sewage treatment plant

STP type:

Municipal Sewage Treatment Plant

STP effluent (m³/day): 2

Conditions and measures related to treatment of waste (including article waste)

Waste treatment

Dispose of waste cans and containers according to local regulations.

Other conditions affecting environmental exposure

Local marine water dilution factor: 100

Local freshwater dilution factor: 10

Receiving surface water flow: 18000 m³/day

Covers indoor and outdoor use

1.2. CS2: Worker Contributing Scenario: Material transfers (PROC8a)

Process Categories

Transfer of substance or mixture (charging and discharging) at non-dedicated facilities (PROC8a)

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure < 0,5 kPa at STP

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Technical and organisational conditions and measures

Technical and organisational measures

Avoid carrying out activities involving exposure for more than 4 hours per day.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear chemically resistant gloves (tested to EN374) in combination with "basic" employee training.

Other conditions affecting worker exposure

Temperature: Assumes use at not more than 20 °C above ambient temperature.

1.2. CS3: Worker Contributing Scenario: Rolling, Brushing (PROC10)

Process Categories

Roller application or brushing (PROC10)

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure < 0,5 kPa at STP

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Technical and organisational conditions and measures

Technical and organisational measures

Avoid carrying out activities involving exposure for more than 4 hours per day.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear chemically resistant gloves (tested to EN374) in combination with "basic" employee training.

Other conditions affecting worker exposure

Temperature: Assumes use at not more than 20 °C above ambient temperature.

1.2. CS4: Worker Contributing Scenario: Roller, spreader, flow application (PROC11)

Process Categories

Non industrial spraying (PROC11)

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure < 0,5 kPa at STP

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure**Duration:**

Covers daily exposures up to 8 hours

Technical and organisational conditions and measures**Technical and organisational measures**

Avoid carrying out activities involving exposure for more than 4 hours per day.

Conditions and measures related to personal protection, hygiene and health evaluation**Personal protection**

Wear chemically resistant gloves (tested to EN374) in combination with "basic" employee training.

Wear suitable face shield.

Wear an impervious suit.

Wear a respirator conforming to EN140.

Other conditions affecting worker exposure

Temperature: Assumes use at not more than 20 °C above ambient temperature.

1.2. CS5: Worker Contributing Scenario: Mixing operations - Manual (PROC19)**Process Categories**

Manual activities involving hand contact (PROC19)

Product (article) characteristics**Physical form of product:**

Liquid, vapour pressure < 0,5 kPa at STP

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure**Duration:**

Covers daily exposures up to 8 hours

Technical and organisational conditions and measures**Technical and organisational measures**

Avoid carrying out activities involving exposure for more than 1 hour per day.

Conditions and measures related to personal protection, hygiene and health evaluation**Personal protection**

Wear chemically resistant gloves (tested to EN374) in combination with "basic" employee training.

Other conditions affecting worker exposure

Temperature: Assumes use at not more than 20 °C above ambient temperature.

1.3 Exposure estimation and reference to its source**1.3. CS1: Environment Contributing Scenario (ERC8c, ERC8f)**

protection target	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
freshwater	= 0.0022 mg/L	EUSES	= 0.00022
marine sediment	= 0.00127 mg/L	EUSES	= 0.0128
freshwater sediment	= 0.012 mg/L	EUSES	= 0.0369
marine water	= 2.34E-05 mg/L	EUSES	= 0.029
soil	= 0.00142 mg/kg dry weight	EUSES	= 0.00722

1.3. CS2: Worker Contributing Scenario: Material transfers (PROC8a)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	= 0.84 mg/m ³	ECETOC TRA worker v2.0	0.07
dermal, systemic, long-term	= 0.2742 mg/kg bw/day	ECETOC TRA worker v2.0	= 0.03

1.3. CS3: Worker Contributing Scenario: Rolling, Brushing (PROC10)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	= 5E-07 mg/m ³	ECETOC TRA worker v2.0	< 0.001
dermal, systemic, long-term	= 2.743 mg/kg bw/day	ECETOC TRA worker v2.0	= 0.33

1.3. CS4: Worker Contributing Scenario: Roller, spreader, flow application (PROC11)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	= 0.36 mg/m ³	ECETOC TRA worker v2.0	0.03
dermal, systemic, long-term	= 2.68 mg/kg bw/day	ECETOC TRA worker v2.0	= 0.32

1.3. CS5: Worker Contributing Scenario: Mixing operations - Manual (PROC19)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	= 2E-07 mg/m ³	ECETOC TRA worker v2.0	< 0.001
dermal, systemic, long-term	= 1.414 mg/kg bw/day	ECETOC TRA worker v3	< 0.42
combined routes, systemic, long-term	N/A	ECETOC TRA worker v3	= 0.42

1.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Exposure Scenario

oxirane, mono[(c12-14-alkyloxy)methyl] derivs.

Exposure Scenario, 08/06/2021

Substance identity	
	oxirane, mono[(c12-14-alkyloxy)methyl] derivs.
CAS No.	68609-97-2
INDEX No.	603-103-00-4
EINECS No.	271-846-8
Registration number	01-2119485289-22

Table of contents

1. **ES 1** Widespread use by professional workers; Various products (PC1, PC9a, PC9b)

1. ES 1 Widespread use by professional workers; Various products (PC1, PC9a, PC9b)

1.1 TITLE SECTION

Exposure Scenario name	Professional application of coatings and inks by brush or roller - Professional application of coatings and inks
Date - Version	07/04/2021 - 1.0
Life Cycle Stage	Widespread use by professional workers
Main user group	Professional uses
Sector(s) of use	Professional uses (SU22)
Product Categories	Adhesives, sealants (PC1) - Coatings and paints, thinners, paint removers (PC9a) - Fillers, putties, plasters, modelling clay (PC9b)

Environment Contributing Scenario

CS1	ERC8c
------------	-------

Worker Contributing Scenario

CS2 Mixing operations	PROC5
CS3 Large surfaces - Surfaces - Rolling, Brushing	PROC10
CS4 Large surfaces - Surfaces - Roller, spreader, flow application	PROC11
CS5 Large surfaces - Surfaces - Rolling, Brushing	PROC19

1.2 Conditions of use affecting exposure

1.2. CS1: Environment Contributing Scenario (ERC8c)

Environmental release categories	Widespread use leading to inclusion into/onto article (indoor) (ERC8c)
---	--

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure < 0,5 kPa at STP

Amount used, frequency and duration of use (or from service life)

Release type: Intermittent release

1.2. CS2: Worker Contributing Scenario: Mixing operations (PROC5)

Process Categories	Mixing or blending in batch processes (PROC5)
---------------------------	---

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure < 0,5 kPa at STP

Concentration of substance in product:

Covers percentage substance in the product up to 25 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Technical and organisational conditions and measures

Technical and organisational measures

Ensure operatives are trained to minimise exposures.

Avoid direct eye contact with product, also via contamination on hands.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374.

Other conditions affecting worker exposure

Indoor use
Professional use

Temperature: Covers use at ambient temperatures.

Body parts exposed:

Assumes that potential dermal contact is limited to hands and forearms.

1.2. CS3: Worker Contributing Scenario: Large surfaces - Surfaces - Rolling, Brushing (PROC10)

Process Categories	Roller application or brushing (PROC10)
---------------------------	---

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure < 0,5 kPa at STP

Concentration of substance in product:

Covers percentage substance in the product up to 25 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Technical and organisational conditions and measures

Technical and organisational measures

Ensure operatives are trained to minimise exposures.
Provide extract ventilation to points where emissions occur.
Avoid direct eye contact with product, also via contamination on hands.
Use long handled brushes and rollers.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374.
Wear a respirator conforming to EN140.

Other conditions affecting worker exposure

Indoor use
Professional use

Temperature: Covers use at ambient temperatures.

1.2. CS4: Worker Contributing Scenario: Large surfaces - Surfaces - Roller, spreader, flow application (PROC11)

Process Categories	Non industrial spraying (PROC11)
---------------------------	----------------------------------

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure < 0,5 kPa at STP

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Frequency:

For each use, avoid using for more than < 4 h/event

Technical and organisational conditions and measures

Technical and organisational measures

Ensure operatives are trained to minimise exposures.
Provide extract ventilation to points where emissions occur.
Avoid direct eye contact with product, also via contamination on hands.
Use long handled brushes and rollers.
Other skin protection measures such as impervious suits and face shields may be required during high dispersion activities which are likely to lead to substantial aerosol release, e.g. spraying.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374.
Wear a respirator conforming to EN140.

Other conditions affecting worker exposure

Indoor use
Professional use

Temperature: Covers use at ambient temperatures.

1.2. CS5: Worker Contributing Scenario: Large surfaces - Surfaces - Rolling, Brushing (PROC19)**Process Categories**

Manual activities involving hand contact (PROC19)

Product (article) characteristics**Physical form of product:**

Liquid, vapour pressure < 0,5 kPa at STP

Concentration of substance in product:

Covers percentage substance in the product up to 25 %.

Amount used, frequency and duration of use/exposure**Duration:**

Covers daily exposures up to 8 hours

Frequency:

For each use, avoid using for more than < 1 h/event

Technical and organisational conditions and measures**Technical and organisational measures**

Ensure operatives are trained to minimise exposures.
Provide extract ventilation to points where emissions occur.
Avoid direct eye contact with product, also via contamination on hands.
Use long handled brushes and rollers.

Conditions and measures related to personal protection, hygiene and health evaluation**Personal protection**

Wear suitable gloves tested to EN374.

Other conditions affecting worker exposure

Indoor use
Professional use

Temperature: Covers use at ambient temperatures.

1.3 Exposure estimation and reference to its source**1.3. CS2: Worker Contributing Scenario: Mixing operations (PROC5)**

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	= 9.3 mg/m ³	ECETOC TRA worker v2.0	= 0.674
dermal, systemic, long-term	= 0.007 mg/kg bw/day	ECETOC TRA worker v2.0	= 0.002

Additional information on exposure estimation:

If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to EN374.

1.3. CS3: Worker Contributing Scenario: Large surfaces - Surfaces - Rolling, Brushing (PROC10)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
---	----------------	--------------------	-----------------------------------

inhalative, local, short-term	= 2.325 mg/m ³	ECETOC TRA worker v2.0	= 0.168
dermal, systemic, long-term	= 0.137 mg/kg bw/day	ECETOC TRA worker v2.0	= 0.035

Additional information on exposure estimation:

If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to EN374.

1.3. CS4: Worker Contributing Scenario: Large surfaces - Surfaces - Roller, spreader, flow application (PROC11)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, local, short-term	= 0.36 mg/m ³	ECETOC TRA worker v2.0	= 0.03
dermal, systemic, long-term	= 2.68 mg/kg bw/day	ECETOC TRA worker v2.0	= 0.32

Additional information on exposure estimation:

If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to EN374.

1.3. CS5: Worker Contributing Scenario: Large surfaces - Surfaces - Rolling, Brushing (PROC19)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, local, long-term	= 2E-07 mg/m ³	ECETOC TRA worker v2.0	< 0.001
dermal, systemic, long-term	= 1.414 mg/kg bw/day	ECETOC TRA worker v2.0	= 0.42

Additional information on exposure estimation:

If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to EN374.

1.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.